


FL 40-PowerCross Plus SP

Convincing along the whole line



Selection PRO



TECHNICAL DATA	FL 40-POWERCROSS PLUS SP	FEATURES
Self-levelling range	± 3°	<ul style="list-style-type: none"> · 1 Laser cross · Laser lines switchable separately · TILT function for manual use · Visual alarm when out of level · Use with receiver FR 75-MM / FR 55 / 55-M (optional) · Multi-functional mount <ul style="list-style-type: none"> · height adjustable · for wall-hanging with screw · strap attachment · strong magnet on back side · for tripod fixing with 5/8" or 1/4" thread
Accuracy	± 3 mm / 10 m	
Working range without receiver	30 m* (radius)	
Working range with receiver (optional)	80 m	
Fan angle horizontal	135°	
Fan angle vertical	150°	
Power supply	4 x AA Alkaline	
Operating time (all lines switched on)	20 h	
Dust / water protection	IP 54	
Laser diode / class	red / 2	
Temperature range	-10 °C to +45 °C	
Weight (instrument with battery)	0,4 kg	
*depending on room illumination		

SUPPLIED WITH FL 40-POWERCROSS PLUS SP

ART-NO. 541510

- Multi-functional mount
- 4 x AA Alkaline battery
- Padded bag

OPTIONAL

ART-NO. 541511

- Charger
- Li-Ion batteries